

Before Engine Start

Flight Controls	Check
Cyclic Control Stick.....	Centered
Mixture Control.....	Rich
Carburetor Heat Control	Cold

Engine Start

Master Battery	On
Generator Switch	On
Fuel Switch	On
Throttle	Slightly Above Idle
Mixture	Rich
Starter	DEPRESS
Ignition Switch	Both

After Engine Start

Engine	Idle
Oil Pressure	Check 65 PSI
Throttle	Increase
Engine RPM	2200 RPM
Oil Temperature	Check 40 C Minimum
Throttle	Increase
Engine RPM	3100 RPM

Magneto Test

Engine RPM	Check
Ignition Switch	Select L
Engine RPM Value Drop	Check
Ignition Switch	Both
Engine RPM Value	Check Returns to Normal
Ignition Switch	Select R
Engine RPM Value Drop	Check

Hover

Clearance.....	Obtain
Hover Taxi	Slowly

Take Off

Collective	Increase
Cyclic	Forward
Rotation.....	30 KIAS Then Apply Backward Cyclic to Climb
Climb Speed	45-50 KIAS

Cruise

Engine Temperatures and Pressures.....	Check
Carburetor Heat Control	As Required
Fuel Quantity.....	Check

Approach

Approach Speed	50 KIAS
Carburetor Heat Control	As Required
Descent Rate	500 FT/MIN

Landing

Flare	At 50 FT
Collective	Increase

Taxi In

Clearance.....	Obtain
Hover Taxi	Slowly

Parking

Engine	Idle
Cyclic Control Stick.....	Centered
Mixture	Cut-Off
Ignition Switch	Off
Main Rotor Pitch (Raise Collective).....	Increase
Generator Switch	Off
Master Battery.....	Off